


Product Data Sheet

7550-4030G 3'X100' 11 Stake 60 gr. - Green Stripe

Silt Fence

60 Gram Green Stripe Contractor Grade 10' OC

Earthsavers contractor grade 60 gram silt fence is made of 100% polypropylene woven fibers. Earthsavers meets or exceeds the properties listed below.

Typical Properties	Test Method	Typical Values	
		English	Metric
Material		Woven Black Polypropylene Fibers	
Grab Tensile	ASTM D-4632	80 LBS	36.28 Kg
Grab Elongation	ASTM D-4632	15%	
CBR Puncture	ASTM D-6241	200 lbs	90.7 Kg
Trapezoid Tear	ASTM D-4533	50 lbs	22.7 Kg
Apparent Opening Size	ASTM D-4751	30 Sieve (.023")	.58 mm
Permitivity	ASTM D-4491	0.05 Sec	
Ultraviolet Exposure	ASTM D-4355	70% after 500 Hours	

- Silt fence is a temporary sediment barrier designed to pond sediment-laden water and allow the sediment to fall out of suspension.
- Fabricated in the USA.



Disclaimer: EarthSaver assumes no responsibility for the completeness or accuracy of this information. EarthSaver disclaims any and all implied, expressed or statutory standard should not be considered engineering advice. Always consult the project engineer for specific requirements. The end user assumes sole responsibility for the use of this information and product. The material property values listed above are subject to change without notice.



i. This document

www.earth-savers.com

PO Box 2083 Woodland CA, 95776 • Toll Free (866) WATTLES • Fax (530) 668-5140