This data supercedes all previous data. Last Updated 6/10/2021



Product Data Sheet			
3300-4100 16" x 24" min 8oz Nonwoven Gravel BLK			
3300-4105 16" x 24" min 8oz NW FILLED Gravel BLK			

8 oz Non-Woven Gravel Bag

Earthsavers 8 oz Non-Woven Gravel Bags are intended to be filled with gravel and used for purposes such as flood control, ballast, and other applications.

Typical Properties	Test Method	Minimum Average Roll Value (MARV)	
Typical Properties		English	Metric
Material		Polypropylene	
Grab Tensile	ASTM D-4632	205 lbs	912 N
Grab Elongation	ASTM D-4632	50%	
CBR Puncture	ASTM D-6241	500 lbs	2,224 N
Trapezoid Tear	ASTM D-4533	80 lbs	356 N
Apparent Opening Size	ASTM D-4751	80 U.S. Sieve	0.18 mm
Flow Rate	ASTM D-4751	95 gal/min/ft ²	3,870 L/min/m ²
Permitivity	ASTM D-4491	1.4 sec ⁻¹	
Ultraviolet Exposure	ASTM D-4355	70% at 500 hours	

• For 3300-4105, FILLED Gravel is from 3/8" to 3/4" in diameter, clean and free clay balls, organic matter and other deleterious materials. Filled and sewn closed with a bag weight from 30 to 50 pounds.



FILLED Gravel Bag pictured.







Disclaimer: EarthSaver assumes no liability for the completeness or accuracy of this information. EarthSavers disclaims any and all implied, expressed or statutory standards, guarantees or warranties. This document should not be considered engineering advice. Always consult the project engineer for specific requirements. The end user assumes sole responsibility for the use of this information and product. The material property values listed above are subject to change without notice.