This data supercedes all previous data. Last Updated 2/22/2018



| Product Data Sheet | |
|--|--|
| 3300-4100 18" x 30" 8oz Nonwoven Gravel BLK | |
| 3300-4105 18" x 30" 8oz NW FILLED Gravel BLK | |

8 oz Non-Woven Gravel Bag

Earthsavers 8 oz Non-Woven Gravel Bags are intended to be filled with gravel and used for purposes such as flood control, ballast, and other applications.

| Typical Properties | Test Method | Typical Values | |
|-----------------------|-------------|----------------------------|----------------------------|
| | | English | Metric |
| Material | | Polypropylene | |
| Grab Tensile | ASTM D-4632 | 205 lbs | 912 N |
| Grab Elongation | ASTM D-4632 | 50% | |
| CBR Puncture | ASTM D-6241 | 500 lbs | 2,224 N |
| Trapezoid Tear | ASTM D-4533 | 80 lbs | 356 N |
| Apparent Opening Size | ASTM D-4751 | 80 U.S. Sieve | 0.18 mm |
| Flow Rate | ASTM D-4751 | 95 gal/min/ft ² | 3,870 L/min/m ² |
| Permitivity | ASTM D-4491 | 1.4 sec ⁻¹ | |
| Ultraviolet Exposure | ASTM D-4355 | 70% at 500 hours | |

• For 3300-4105, FILLED Gravel is from 3/8" to 3/4" in diameter, clean and free clay balls, organic matter and other deleterious materials. Filled and sewn closed with a bag weight from 30 to 50 pounds.



FILLED Gravel Bag pictured.







Disclaimer: EarthSaver assumes no liability for the completeness or accuracy of this information. EarthSavers disclaims any and all implied, expressed or statutory standards, guarantees or warranties. This document should not be considered engineering advice. Always consult the project engineer for specific requirements. The end user assumes sole responsibility for the use of this information and product. The material property values listed above are subject to change without notice.

www.earth-savers.com
PO Box 2083 Woodland CA, 95776 ● Toll Free (866) WATTLES ● Fax (530) 668-5140

JO copyright 2014