



Product Data Sheet	
7600-2320	3X500' - Fabric Only- Solid Orange
7600-2360	3X1500' - Fabric Only- Solid Orange

Silt Fence

Orange Fabric Only Roll

Earthsavers orange silt fence is a superior quality construction silt fence. The orange color provides for double duty use as a high visibility barrier fence. Earthsavers orange silt fence meets Caltrans 2015 Section 96-1.02E requirements for Silt Fence Fabric.

Typical Properties	Test Method	Typical Values	
		English	Metric
Material		Orange - Polypropylene	
Grab Tensile	ASTM D-4632	135 lbs	61.2 Kg
Grab Elongation	ASTM D-4632	Minimum 15%	
Mullen Burst	ASTM D-3786	294 PSI	2027 kPa
Puncture	ASTM D-4888	85 lbs	38.6 Kg
Trapezoid Tear - MD	ASTM D-4533	75.2 lbs	34.1 Kg
Trapezoid Tear - XD	ASTM D-4533	61.3 lbs	27.8 Kg
Apparent Opening Size	ASTM D-4751	30 Sieve (.023")	.58 mm
Flow Rate	ASTM D-4491	15.5 Gal/Min/ft ²	631.6 L/Min/m ²
Permitivity	ASTM D-4491	0.2 Sec ⁻¹	
Ultraviolet Exposure	ASTM D-4355	80% after 500 Hours	

- Silt fence is a temporary sediment barrier designed to pond sediment-laden water and allow the sediment to fall out of suspension.
- Meets ASTM D6461 - Standard Specification for Silt Fence Materials



Disclaimer: EarthSaver assumes no liability for the completeness or accuracy of this information. EarthSavers disclaims any and all implied, expressed or statutory standards, guarantees or warranties. This document should not be considered engineering advice. Always consult the project engineer for specific requirements. The end user assumes sole responsibility for the use of this information and product. The material property values listed above are subject to change without notice.

www.earth-savers.com
 PO Box 2083 Woodland CA, 95776 • Toll Free (866) WATTLES • Fax (530) 668-5140