This data supercedes all previous data. Last Updated 6/18/2020



Product Data Sheet

3000-4000-Y 19" x 28" Monofilament Gravel Bag - Yellow (250/box)

Yellow Woven Gravel Bag

Earthsavers' YELLOW Woven Gravel Bags are made of High Density Polyethylene (HDPE). Our YELLOW Woven Gravel Bags meet or exceed the following properties:

Properties	Test Method	Typical Values
Material		HDPE
Size		19" x 28"
Color		Yellow
Fabric Weight	D5261	5 oz/SY
Wide Width Tensile (MD/TD)	D4595	2,400/1,680 lbs
Grab Tensile (MD/TD)	D4632	365/200 lbs
Trapazoid Tear (MD/TD)	D4533	115/75 lbs
Puncture	D4833	90 lbs
Mullen Burst	D3786	450 psi
Permitivity	D4491	2.1 (sec -1)
Water Flow Rate	D4491	145 gpm/ft2
Permeability	D4491	0.14 cm/sec
A.O.S. Sieve	D4751	40 US Sieve (0.425 mm)
UV Stabilization % @ 500 hrs	D4355	>90%

The numeric values listed above are typcial.

• Inside dimensions are 17" x 27".







Disclaimer: EarthSaver assumes no liability for the completeness or accuracy of this information. EarthSavers disclaims any and all implied, expressed or statutory standards, guarantees or warranties. This document should not be considered engineering advice. Always consult the project engineer for specific requirements. The end user assumes sole responsibility for the use of this information and product. The material property values listed above are subject to change without notice.

www.earth-savers.com
PO Box 2083 Woodland CA, 95776 ● Toll Free (866) WATTLES ● Fax (530) 668-5140

jwo copyright 2020

This data supercedes all previous data. Last Updated 6/18/2020



Product Data Sheet

3000-4000 19" x 28" Monofilament Gravel Bag - Orange (250/box)

Orange Monofilament Gravel Bag

Earthsavers' Orange Monofilament Gravel Bags are made of monofilament polypropylene material. Our Orange Monofilament Gravel Bags meet or exceed the following properties:

Properties	Test Method	Typical Values
Material		Polypropylene
Size		19" x 28"
Color		Orange
Fabric Weight	D5261	5 oz/SY
Grab Tensile (MD/TD)	D4632	350/220 lbs
Trapazoid Tear (MD/TD)	D4533	145/75 lbs
Puncture	D4833	110 lbs
Mullen Burst	D3786	400 psi
Water Flow Rate	D4491	195 gpm/ft2
UV Stabilization % @ 2,000 hrs	D4355	>70%







Disclaimer: EarthSaver assumes no liability for the completeness or accuracy of this information. EarthSavers disclaims any and all implied, expressed or statutory standards, guarantees or warranties. This document should not be considered engineering advice. Always consult the project engineer for specific requirements. The end user assumes sole responsibility for the use of this information and product. The material property values listed above are subject to change without notice.

www.earth-savers.com
PO Box 2083 Woodland CA, 95776 ● Toll Free (866) WATTLES ● Fax (530) 668-5140

jwo copyright 2020